

Atrix

Sunwoda Atrix series adopts a flexible modular design, which can be expanded from 5 kWh of a single module to 120 kWh of 24 battery modules.



Flexible application

- Optimized for stack and build-in cabinet installation



Easy to install

- Plug and play
- Compact and Light
- 2 persons installation



Excellent performance

- 100% DOD
- Operate at -10°C without any limitation and attenuation



Battery APP (Optional)


- Real time monitoring
- Remote maintenance and upgrades (Optional)

Specifications

Model	Atrix-5	Atrix-10	Atrix-15	Atrix-20
Nominal energy	5kWh	10kWh	15kWh	20kWh
Usable energy (100% DOD)	5kWh	10kWh	15kWh	20kWh
Rated voltage	51.2V	51.2V	51.2V	51.2V
Charge/discharge cut off voltage	44.8V~55.2V	44.8V~55.2V	44.8V~55.2V	44.8V~55.2V
Roundtrip efficiency	>98%	>98%	>98%	>98%
Rated charge/discharge current	50A/50A	100A/100A	150A/150A	200A/200A
Max. charge/discharge current	100A/100A	180A/180A	200A/200A	200A/200A
Communication interface	CAN 2.0/RS485			
Scalability	Max. 24 in parallel, Max. 120 kWh			

Operating conditions

Installation location	Indoor
Operating temperature	Discharging:-4°F to 122°F (-20°C to 50°C), Charging:14°F to 122°F (-10°C to 50°C)
Humidity	10% to 95%, non-condensation
Dimensions	482*135*433/PACK (W*H*D, mm)
Weight	45kg/90kg/135kg/180kg
Enclosure protection rating	IP20
Altitude	<4000m
Cooling	Natural convection
Warranty	10 years*
Certificates	IEC62619/CE/CEI 0-21/UL1973/ FCC/UN38.3



* DC Usable Energy, Test conditions: 100% DOD, 0.2C charge & discharge at 25°C.

* Charge/discharge derating occurs when the operating temperature from -10°C to 5°C.